





























WOHNRAUM BE- UND ENTLÜFTUNG

		DN 75	DN 110	DN 110	DN 125	DN 160
 <p>belüftetes Dach</p>	 <p>Hart-PVC-Flansch</p>	 234 261 ø285 KF 6040	 310 345,5 ø350 KF 6050	 270 345,5 ø350 KF 6060	 270 411 ø366 KF 6070	 300 460 ø446 KF 6080
	 <p>Bitumen-Manschette (Manschettenmaß 500 x 500 mm)</p>	 234 216 ø285 KF 6041	 310 345,5 ø350 KF 6051	 270 345,5 ø350 KF 6061	 270 411 ø366 KF 6071	 300 460 ø446 KF 6081
	 <p>Klemm-Flansch</p>		 310 345,5 ø350 KF 6052		 270 411 ø366 KF 6072	
		eingeschränkt verlängerbar, manuell trennen, stumpf verkleben		Sanierungs-Lüfter für muffenlose Röhre eingeschränkt verlängerbar, manuell trennen, stumpf oder mit optionaler Verbindungsmuffe verkleben		uneingeschränkt verlängerbar

		DN 75	DN 110	DN 110	DN 125	DN 160
 <p>unbelüftetes Dach</p>	 <p>Hart-PVC-Flansch Unterteil</p>	 255 ø285 KF 6500	 299 ø348,5 KF 6510	Kein Unterteil notwendig	 299 ø363 KF 6520	 400 ø446 KF 6570
	 <p>Bitumen-Manschette Unterteil (Manschettenmaß 500 x 500 mm)</p>	 255 ø285 KF 6501	 299 ø348,5 KF 6511	Kein Unterteil notwendig	 299 ø363 KF 6521	 400 ø446 KF 6571

		DN 75	DN 110	DN 110	DN 125	DN 160
	<p>Oberrohrverlängerungen (individuell kürzbar)</p>	 250 KF 6806	 340 KF 6807	 340 KF 6807	 300 KF 6808	Nach Abstimmung mit Klöber Technik unter: 02333-9877-164 KF 6570
	<p>Dämmpaket-Rohrverlängerungen (individuell kürzbar)</p>	 500 KF 6836	 500 KF 6837	 110 KE 8006	 500 KF 6838	Nach Abstimmung mit Klöber Technik unter: 02333-9877-164 KF 6570
		>194 mm	>275 mm	>275 mm	>235 mm	>280 mm
		KF 6836	KF 6837	KE 8006	KF 6838	KF 6570